



SPECIFICATION & SIZE CHART FOR VRV AIR CONDITION GRADE COPPER TUBES

Sr. No.	CODE	DESCRIPTION SIZE NIPPON TUBE HALF HARD VRV/VRF COMPATIBLE COPPER TUBES	TEMPER	WEIGHT PER METER (IN KGS.)	WEIGHT 10 FEET (IN KGS)
1	VRV / VRF	1/4" (6.35mm) X 21 Swg (0.8 mm)	Half hard	0.127	0.387
2	VRV / VRF	3/8" (9.52mm) X 21 Swg (0.8 mm)	Half hard	0.199	0.607
3	VRV / VRF	1/2" (12.7mm) X 20 Swg (0.91mm)	Half hard	0.301	0.925
4	VRV / VRF	5/8" (15.88mm) X 19 Swg (0.99 mm)	Half hard	0.425	1.296
5	VRV / VRF	3/4" (19.05mm) X 19 Swg (1.0 mm)	Half hard	0.515	1.570
6	VRV / VRF	7/8" (22.2mm) X 19 Swg (1.0 mm)	Half hard	0.605	1.850
7	VRV / VRF	1/0" (25.4mm) X 19 Swg (1.0 mm)	Half hard	0.696	2.140
8	VRV / VRF	1 1/8" (28.6mm) X 19 Swg (1.0 mm)	Half hard	0.787	2.400
9	VRV / VRF	1 1/4" (31.8mm) X 18 Swg (1.21 mm)	Half hard	1.040	3.200
10	VRV / VRF	1 3/8" (34.9mm) X 18 Swg (1.2 mm)	Half hard	1.155	3.500
11	VRV / VRF	1 1/2" (38.1mm) X 18 Swg (1.21 mm)	Half hard	1.255	3.860
12	VRV / VRF	1 5/8" (41.3mm) X 17 Swg (1.42 mm)	Half hard	1.582	4.860
13	VRV / VRF	1 3/4" (44.45mm) X 16 Swg (1.62 mm)	Half hard	1.950	5.960
14	VRV / VRF	2 1/8" (54.0mm) X 16 Swg (1.62 mm)	Half hard	2.400	7.300

SOFT TEMPER 15.24 MTR/ 50 FEET PANCAKE COIL TUBE WEIGHT CHART

Sr. No.	CODE	DESCRIPTION SIZE - COPPER TUBE VRV / VRF PAN CAKE SOFT COIL	TEMPER	15.24 Mtr /50 FEET VRV / VRF COIL WEIGHT	
				WEIGHT PER METER (IN KGS.)	PER COIL WEIGHT
1	VRV / VRF	1/4" (6.35mm) X 21 Swg (0.8 mm)	Soft	0.127	1.900
2	VRV / VRF	3/8" (9.52mm) X 21 Swg (0.8 mm)	Soft	0.199	3.000
3	VRV / VRF	1/2" (12.7mm) X 21 Swg (0.8 mm)	Soft	0.301	4.100
4	VRV / VRF	5/8" (15.88mm) X 21 Swg (0.8 mm)	Soft	0.382	5.200
5	VRV / VRF	3/4" (19.05mm) X 21 Swg (0.8 mm)	Soft	0.463	6.370
6	VRV / VRF	7/8" (22.2mm) X 21 Swg (0.8 mm)	Soft	0.544	8.300

WE CAN ALSO CUSTOMIZED SIZE IF REQUIRED BY CUSTOMER